



Report No.:

Test Time: 2021-04-10 13:17

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: RAD-S-CIS-3.3000.24.-.12

Luminous Length (mm): -53

Luminous Width (mm): -53

Luminous Height (mm): 70

Voltage: 24.0 V

Current: 0.142 A

Power: 3.40 W

Power Factor: 1.000

Photometric Results

CIE Class: Direct

Measurement Flux: 311.9 lm

Downward Ratio: 100%

Total Rated Lamp Lumens: 311.9 lm

Efficiency: 100%

Upward Ratio: 0%

Field Angle(C0/C180,C90/C270,C45/C225,C135/315): 26.0, 25.9, 26.4, 26.1

Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 16.1, 16.2, 16.3, 15.9

Luminaire Efficacy Rating (LER): 91.78

Central Intensity: 3655.13 cd

Max. Intensity: 3697.67 cd

Pos of Max. Intensity: H290 V1


S/MH(C0/C180): 0.28

S/MH(C90/C270): 0.28

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 10.0

Test Lab: Svet-lab

Test Type: TYPE C

Temperature:

Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0


Test Device: LSG-1700B

Distance: 9.600 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve




C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)




Isocandela (rectangle)



Imax (100%): 3698 cd

(10%): 370 cd	(16%): 592 cd
(25%): 924 cd	(40%): 1479 cd
(63%): 2330 cd	(100%): 3698 cd

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 37.0 lx

(1%): 0.4 lx	(2%): 0.7 lx
(5%): 1.8 lx	(10%): 3.7 lx
(20%): 7.4 lx	(50%): 18.5 lx
(100%): 37.0 lx	


C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Illuminance at a Distance




Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 3655.1 lx
 (1%): 36.6 lx (2%): 73.1 lx
 (5%): 182.8 lx (10%): 365.5 lx
 (20%): 731.0 lx (50%): 1827.6 lx
 (100%): 3655.1 lx

The Average Illuminance Effective Figure




UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
3H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=4H Y=2H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
3H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=8H Y=4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=12H Y=4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
Variations with the observer position at spacings:										
S=1.0H	-1.\$/6.7					-1.\$/6.5				
S=1.5H	-1.\$/9.5					-1.\$/9.3				
S=2.0H	-1.\$/11.5					-1.\$/11.3				

Calculate in accordance with CIE Pub.117. The table is revised with 312lm ($8\log(F/F_0) = -4.0$).

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM




ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	137	44.0
FL (0°-30°)	135	43.3
FM (30°-60°)	2	0.7
FH (60°-80°)	0	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	175	56.0
BL (0°-30°)	172	55.1
BM (30°-60°)	3	0.9
BH (60°-80°)	0	0.0
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

LCS Graph



Back Light

Forward Light

Scale= MAX LCS%

Trapped Light:NA,NA

C Plane (°):0.0-360.0: 10.0

Test Lab: Svet-lab

Test Type: TYPE C

Temperature:

Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0

Test Device: LSG-1700B

Distance: 9.600 m

Humidity:

Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	3632.4	3.5	3.5	1.11	1.11
1.0-2.0	3599.5	10.3	13.8	3.31	4.43
2.0-3.0	3511.4	16.8	30.6	5.39	9.81
3.0-4.0	3357.0	22.5	53.1	7.21	17.02
4.0-5.0	3133.3	27.0	80.0	8.64	25.66
5.0-6.0	2822.6	29.7	109.7	9.51	35.18
6.0-7.0	2451.7	30.4	140.1	9.76	44.93
7.0-8.0	2051.1	29.4	169.5	9.41	54.35
8.0-9.0	1638.9	26.6	196.1	8.52	62.87
9.0-10.0	1262.3	22.8	218.9	7.33	70.19
10.0-11.0	930.2	18.6	237.5	5.96	76.15
11.0-12.0	660.1	14.4	251.9	4.63	80.78
12.0-13.0	465.3	11.0	263.0	3.54	84.32
13.0-14.0	321.4	8.2	271.2	2.64	86.96
14.0-15.0	223.1	6.1	277.3	1.96	88.92
15.0-16.0	161.2	4.7	282.1	1.52	90.44
16.0-17.0	119.9	3.7	285.8	1.20	91.63
17.0-18.0	93.2	3.1	288.9	0.99	92.62
18.0-19.0	74.9	2.6	291.5	0.84	93.46
19.0-20.0	62.0	2.3	293.7	0.73	94.18
20.0-21.0	52.8	2.0	295.8	0.65	94.83
21.0-22.0	45.1	1.8	297.6	0.58	95.42
22.0-23.0	38.8	1.6	299.2	0.52	95.94
23.0-24.0	33.4	1.5	300.7	0.47	96.41
24.0-25.0	28.9	1.3	302.0	0.42	96.83
25.0-26.0	25.3	1.2	303.2	0.38	97.21
26.0-27.0	22.1	1.1	304.3	0.35	97.56
27.0-28.0	19.5	1.0	305.2	0.32	97.87
28.0-29.0	17.2	0.9	306.1	0.29	98.16
29.0-30.0	15.1	0.8	307.0	0.26	98.42
30.0-31.0	13.2	0.7	307.7	0.24	98.66
31.0-32.0	11.6	0.7	308.4	0.21	98.87
32.0-33.0	10.1	0.6	309.0	0.19	99.06
33.0-34.0	8.7	0.5	309.5	0.17	99.23
34.0-35.0	7.5	0.5	309.9	0.15	99.38
35.0-36.0	6.4	0.4	310.4	0.13	99.51

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab


Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	5.4	0.4	310.7	0.11	99.62
37.0-38.0	4.4	0.3	311.0	0.09	99.72
38.0-39.0	3.6	0.2	311.2	0.08	99.80
39.0-40.0	2.8	0.2	311.4	0.06	99.86
40.0-41.0	2.1	0.2	311.6	0.05	99.91
41.0-42.0	1.5	0.1	311.7	0.04	99.94
42.0-43.0	1.0	0.1	311.8	0.02	99.97
43.0-44.0	0.6	0.0	311.8	0.01	99.98
44.0-45.0	0.3	0.0	311.8	0.01	99.99
45.0-46.0	0.2	0.0	311.9	0.00	100.00
46.0-47.0	0.1	0.0	311.9	0.00	100.00
47.0-48.0	0.1	0.0	311.9	0.00	100.00
48.0-49.0	0.0	0.0	311.9	0.00	100.00
49.0-50.0	0.0	0.0	311.9	0.00	100.00
50.0-51.0	0.0	0.0	311.9	0.00	100.00
51.0-52.0	0.0	0.0	311.9	0.00	100.00
52.0-53.0	0.0	0.0	311.9	0.00	100.00
53.0-54.0	0.0	0.0	311.9	0.00	100.00
54.0-55.0	0.0	0.0	311.9	0.00	100.00
55.0-56.0	0.0	0.0	311.9	0.00	100.00
56.0-57.0	0.0	0.0	311.9	0.00	100.00
57.0-58.0	0.0	0.0	311.9	0.00	100.00
58.0-59.0	0.0	0.0	311.9	0.00	100.00
59.0-60.0	0.0	0.0	311.9	0.00	100.00
60.0-61.0	0.0	0.0	311.9	0.00	100.00
61.0-62.0	0.0	0.0	311.9	0.00	100.00
62.0-63.0	0.0	0.0	311.9	0.00	100.00
63.0-64.0	0.0	0.0	311.9	0.00	100.00
64.0-65.0	0.0	0.0	311.9	0.00	100.00
65.0-66.0	0.0	0.0	311.9	0.00	100.00
66.0-67.0	0.0	0.0	311.9	0.00	100.00
67.0-68.0	0.0	0.0	311.9	0.00	100.00
68.0-69.0	0.0	0.0	311.9	0.00	100.00
69.0-70.0	0.0	0.0	311.9	0.00	100.00
70.0-71.0	0.0	0.0	311.9	0.00	100.00
71.0-72.0	0.0	0.0	311.9	0.00	100.00

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:



C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C10.0	C20.0	C30.0	C40.0	C50.0	C60.0	C70.0	C80.0	C90.0
G0.0	3655.1	3648.0	3645.1	3639.9	3631.7	3629.5	3622.0	3625.2	3622.8	3632.5
G1.0	3624.5	3618.3	3625.1	3625.4	3630.2	3636.3	3641.6	3642.3	3646.4	3649.9
G2.0	3545.3	3532.6	3551.1	3542.7	3560.4	3573.6	3586.8	3586.9	3605.1	3603.1
G3.0	3379.9	3365.1	3374.9	3359.1	3383.0	3391.5	3408.1	3404.4	3440.0	3452.8
G4.0	3156.0	3108.0	3125.9	3089.9	3116.3	3126.8	3164.6	3160.0	3203.2	3197.5
G5.0	2841.9	2776.6	2788.8	2741.5	2784.3	2794.3	2837.3	2799.1	2856.8	2830.0
G6.0	2451.4	2367.4	2375.1	2313.4	2335.3	2338.4	2387.1	2353.0	2395.7	2387.1
G7.0	2038.1	1942.7	1944.1	1875.3	1904.2	1918.3	1960.9	1906.9	1955.1	1940.0
G8.0	1614.1	1506.8	1548.9	1446.1	1508.1	1461.7	1535.2	1458.8	1534.2	1480.1
G9.0	1216.9	1145.7	1154.9	1102.9	1113.2	1114.7	1128.4	1087.1	1114.4	1112.2
G10.0	906.6	830.4	841.8	802.4	822.7	811.8	827.5	790.4	808.9	792.1
G11.0	618.5	576.9	577.5	558.1	578.4	571.9	578.7	538.0	546.3	538.6
G12.0	432.6	398.6	406.9	393.0	406.2	412.9	410.6	380.4	381.6	367.5
G13.0	295.7	275.9	283.2	281.5	293.1	293.9	294.4	269.4	264.8	254.9
G14.0	203.2	190.3	198.3	196.1	205.3	207.5	205.5	188.1	185.1	177.3
G15.0	149.8	137.9	146.1	146.0	154.3	155.6	153.4	139.9	137.1	129.1
G16.0	111.4	105.0	109.7	109.4	112.5	113.2	112.3	104.2	100.9	96.9
G17.0	89.4	84.1	87.5	85.8	88.2	87.6	87.2	82.2	80.5	75.8
G18.0	73.4	68.4	71.1	69.8	71.3	68.8	69.8	67.2	64.4	62.7
G19.0	62.6	57.9	59.0	57.7	56.5	56.1	56.3	55.1	53.0	52.3
G20.0	53.6	48.9	51.2	49.3	48.1	47.2	48.5	47.0	45.3	45.3
G21.0	46.3	42.9	43.9	42.4	42.0	40.7	42.5	40.2	39.5	39.8
G22.0	40.0	37.3	37.6	36.6	35.3	36.0	36.0	36.5	33.2	35.0
G23.0	34.8	33.4	33.2	32.3	30.7	31.3	31.5	31.2	29.1	30.5
G24.0	30.5	29.0	29.1	26.6	27.2	27.9	27.9	27.0	26.4	25.9
G25.0	27.2	25.3	25.7	24.1	24.0	23.9	24.0	23.3	24.0	23.4
G26.0	23.5	22.6	22.4	21.4	21.6	21.6	21.8	20.9	21.2	20.2
G27.0	21.0	19.8	20.0	18.9	18.6	19.4	18.8	19.2	17.9	17.8
G28.0	18.6	18.3	17.6	17.8	17.0	16.5	17.1	16.7	16.6	15.9
G29.0	17.3	16.7	15.4	14.9	14.3	14.5	15.0	14.5	14.2	14.1
G30.0	14.7	13.7	13.8	13.6	13.0	13.0	12.6	12.7	12.7	12.5
G31.0	13.6	12.4	12.0	11.0	11.0	11.4	10.5	11.6	12.0	10.9
G32.0	11.9	10.8	10.9	9.9	10.4	10.0	8.7	10.1	10.1	9.0
G33.0	10.4	9.0	9.6	8.7	8.8	8.7	7.3	9.0	8.9	8.7
G34.0	8.6	7.5	8.7	7.6	8.0	7.3	6.7	7.6	7.7	7.8
G35.0	7.5	6.2	7.9	6.2	6.6	6.8	5.1	7.3	6.2	5.5
G36.0	6.4	5.5	6.1	5.5	5.9	5.8	4.8	6.3	6.2	4.7

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C10.0	C20.0	C30.0	C40.0	C50.0	C60.0	C70.0	C80.0	C90.0
G37.0	5.1	4.0	5.0	4.2	5.1	4.6	3.2	5.5	5.0	4.0
G38.0	4.0	3.7	4.4	4.2	3.7	4.1	2.9	3.8	4.1	2.8
G39.0	3.8	2.6	3.1	3.0	3.2	3.2	2.0	3.3	4.3	2.0
G40.0	2.4	2.1	2.5	2.6	2.3	2.2	1.0	3.1	2.6	1.5
G41.0	1.7	2.0	2.7	2.2	2.8	2.5	1.0	2.5	1.7	0.4
G42.0	1.0	1.5	1.6	1.3	1.2	2.0	0.3	1.6	1.0	0.7
G43.0	1.3	0.5	1.3	1.3	0.8	0.7	0.0	1.0	0.7	0.9
G44.0	0.3	0.3	0.4	0.4	0.3	0.4	0.0	0.6	0.0	0.0
G45.0	0.0	0.0	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.1
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 3)

Unit: cd

G\C	C100.0	C110.0	C120.0	C130.0	C140.0	C150.0	C160.0	C170.0	C180.0	C190.0
G0.0	3623.6	3695.9	3671.2	3630.0	3635.8	3628.8	3628.6	3631.9	3655.1	3648.0
G1.0	3650.6	3670.6	3636.4	3578.5	3597.8	3606.1	3621.1	3634.4	3658.1	3645.7
G2.0	3614.6	3617.4	3568.4	3504.3	3540.8	3552.2	3587.5	3604.7	3642.3	3624.5
G3.0	3480.1	3479.9	3388.2	3325.3	3387.9	3417.1	3466.2	3508.6	3572.2	3559.9
G4.0	3244.8	3255.6	3131.9	3084.5	3163.4	3191.8	3274.4	3318.7	3426.4	3438.8
G5.0	2908.6	2951.9	2803.1	2751.0	2843.3	2882.7	2992.9	3049.5	3220.1	3240.8
G6.0	2451.8	2523.4	2355.9	2337.0	2440.2	2477.7	2615.5	2685.5	2889.7	2952.1
G7.0	2027.4	2100.8	1928.8	1911.8	2024.6	2066.6	2203.3	2277.7	2531.4	2600.1
G8.0	1584.1	1634.8	1494.6	1454.8	1622.4	1624.7	1780.0	1814.7	2069.6	2211.3
G9.0	1173.7	1229.2	1085.8	1098.5	1198.3	1250.0	1354.8	1394.3	1657.4	1759.6
G10.0	841.6	899.7	791.7	802.5	885.9	910.7	1000.8	1048.1	1278.5	1352.1
G11.0	569.4	602.6	533.8	536.0	602.4	629.0	698.4	735.4	904.5	983.4
G12.0	387.9	406.6	361.6	368.9	417.5	430.7	486.4	505.8	638.9	690.5
G13.0	271.8	280.4	252.1	252.1	284.8	295.6	329.5	342.1	434.3	479.1
G14.0	187.8	189.6	172.8	171.1	196.5	203.6	223.0	231.4	288.0	312.6
G15.0	137.2	139.8	129.3	127.3	142.4	145.9	160.3	164.4	199.0	220.1
G16.0	101.0	104.1	95.9	96.3	106.2	108.8	116.4	119.6	143.0	161.9
G17.0	80.1	82.4	76.6	74.8	83.9	84.7	89.4	91.6	108.9	117.9
G18.0	65.3	66.8	63.7	61.7	68.0	67.5	72.6	73.2	85.8	94.2
G19.0	53.6	55.8	52.2	53.8	55.9	55.7	58.8	60.7	70.3	75.3
G20.0	46.5	48.0	44.9	45.1	48.6	47.5	51.0	51.7	59.2	63.5
G21.0	40.2	41.3	39.4	38.4	41.6	39.9	43.2	43.4	50.6	54.8
G22.0	35.1	36.1	34.4	33.4	35.4	34.4	37.0	36.7	43.3	46.6
G23.0	30.9	31.5	29.8	29.8	30.0	29.9	32.5	32.4	37.3	40.9
G24.0	26.9	27.2	25.3	24.6	25.6	25.3	27.7	27.6	31.6	34.9
G25.0	23.7	23.3	22.3	22.0	22.4	22.1	24.3	23.8	27.8	30.2
G26.0	21.0	21.3	19.9	19.4	19.7	18.8	20.7	20.0	24.2	26.2
G27.0	18.1	17.6	17.8	16.9	17.0	16.3	18.3	17.6	20.5	23.1
G28.0	15.8	15.9	15.3	14.5	14.8	14.2	16.5	15.5	18.5	20.7
G29.0	14.1	14.1	13.5	12.9	13.3	12.5	14.5	13.0	16.5	17.8
G30.0	12.4	12.5	11.4	11.8	11.5	10.7	12.5	11.3	13.6	16.0
G31.0	10.8	11.3	10.1	9.3	10.0	9.4	10.5	10.2	12.2	14.4
G32.0	9.3	10.4	8.5	8.0	8.3	7.7	9.5	8.9	10.5	12.4
G33.0	7.9	9.0	7.3	6.7	6.6	6.5	8.3	7.3	8.8	11.8
G34.0	6.5	8.1	6.2	6.4	6.0	5.7	6.8	5.7	8.2	10.4
G35.0	5.9	6.7	5.0	5.2	5.1	4.3	6.1	4.8	6.4	8.8
G36.0	4.9	5.3	4.3	4.2	3.8	3.4	4.8	4.0	6.1	8.2

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 4)

Unit: cd

G\C	C100.0	C110.0	C120.0	C130.0	C140.0	C150.0	C160.0	C170.0	C180.0	C190.0
G37.0	4.0	4.6	3.8	3.2	3.3	2.3	4.7	3.2	5.2	6.5
G38.0	3.8	3.6	3.2	2.7	2.4	2.0	3.7	2.0	3.5	5.5
G39.0	2.6	2.9	2.3	1.9	0.7	1.7	2.6	1.3	3.4	4.3
G40.0	1.7	1.5	2.0	1.0	0.6	0.0	1.9	0.6	2.4	3.8
G41.0	1.3	1.0	1.2	0.4	0.8	0.0	1.5	0.0	1.4	3.0
G42.0	1.0	0.2	0.9	0.0	0.0	0.0	0.3	0.0	1.2	2.1
G43.0	0.0	0.0	0.5	0.0	0.0	0.0	0.4	0.0	0.3	1.6
G44.0	0.2	0.0	0.3	0.0	0.0	0.0	0.3	0.0	0.0	1.0
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.5
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.9
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.2
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.3
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 6)

Unit: cd

G\C	C200.0	C210.0	C220.0	C230.0	C240.0	C250.0	C260.0	C270.0	C280.0	C290.0
G0.0	3645.1	3639.9	3631.7	3629.5	3622.0	3625.2	3622.8	3632.5	3623.6	3695.9
G1.0	3637.4	3623.8	3609.4	3598.4	3586.2	3581.6	3578.8	3580.3	3572.4	3697.7
G2.0	3604.3	3584.2	3560.6	3543.5	3524.4	3514.6	3505.1	3510.5	3500.2	3658.4
G3.0	3536.8	3519.6	3493.6	3470.5	3445.9	3433.1	3409.4	3415.4	3395.3	3571.9
G4.0	3421.2	3417.1	3386.0	3361.7	3337.2	3324.9	3305.9	3308.2	3276.1	3421.2
G5.0	3240.9	3254.5	3238.2	3219.9	3180.4	3177.4	3138.9	3136.2	3094.7	3194.7
G6.0	2940.6	2999.4	2986.4	2971.4	2931.4	2924.6	2876.9	2883.0	2833.5	2862.1
G7.0	2613.6	2677.3	2687.2	2671.1	2632.2	2635.0	2580.2	2569.7	2511.3	2498.6
G8.0	2198.0	2309.4	2262.7	2293.3	2223.6	2271.5	2190.7	2218.4	2114.9	2071.1
G9.0	1779.0	1857.0	1863.4	1859.4	1836.1	1854.4	1785.3	1797.9	1704.7	1622.0
G10.0	1388.1	1465.3	1454.9	1467.1	1426.9	1448.4	1399.0	1391.1	1328.4	1249.8
G11.0	994.4	1076.5	1075.8	1071.2	1046.1	1059.5	1004.9	1014.4	968.8	892.5
G12.0	715.2	769.5	774.7	781.4	750.3	767.3	723.4	731.8	690.6	645.5
G13.0	494.1	541.8	547.9	554.8	530.7	532.3	500.9	505.8	487.6	451.8
G14.0	328.9	357.3	362.9	367.7	350.9	360.5	338.8	341.8	324.7	309.2
G15.0	228.2	250.4	253.8	257.9	246.4	251.0	237.1	238.6	229.4	219.2
G16.0	161.9	178.7	177.6	183.4	173.4	183.1	167.9	175.9	164.3	162.8
G17.0	122.1	131.3	134.0	134.0	131.0	133.6	128.7	130.0	125.1	121.2
G18.0	95.3	103.3	103.4	105.1	103.7	106.1	100.8	101.9	99.7	95.7
G19.0	76.6	81.8	82.7	84.5	83.4	85.8	81.8	82.7	81.2	76.9
G20.0	65.5	68.9	69.1	70.5	69.4	72.3	69.2	68.8	68.6	65.3
G21.0	54.9	58.7	58.6	60.3	59.8	61.0	58.7	58.3	58.0	56.6
G22.0	47.1	49.7	49.3	50.1	50.6	51.0	48.6	49.8	49.3	46.8
G23.0	40.2	42.9	42.2	42.9	43.3	43.8	41.7	41.3	42.4	41.1
G24.0	34.1	36.5	36.2	37.7	37.4	37.2	35.1	35.2	35.6	35.3
G25.0	30.4	30.8	31.4	32.3	32.8	32.2	30.8	30.4	30.9	30.4
G26.0	27.0	27.1	27.9	28.9	28.3	27.6	26.6	26.0	27.1	26.9
G27.0	23.2	23.4	24.0	25.3	25.1	24.5	22.7	23.4	24.1	23.8
G28.0	20.7	21.2	21.5	22.2	22.6	22.0	19.6	19.9	21.3	21.0
G29.0	17.9	18.9	18.6	19.2	19.9	19.5	17.1	16.8	18.9	18.8
G30.0	15.6	16.4	15.9	17.2	17.3	17.5	15.4	16.8	16.4	15.9
G31.0	14.3	14.4	14.3	15.4	16.1	15.5	13.0	14.8	14.2	14.6
G32.0	12.8	12.5	12.1	14.1	14.7	13.6	11.8	13.4	11.9	12.4
G33.0	11.3	11.2	11.3	11.9	12.5	12.2	9.4	9.7	10.4	11.1
G34.0	9.7	9.9	9.8	10.4	11.6	10.6	7.8	8.2	8.5	9.6
G35.0	8.7	7.8	7.9	9.6	10.2	9.6	7.6	6.6	7.6	8.1
G36.0	7.3	7.3	7.5	8.3	8.8	8.5	6.1	5.5	6.7	6.7

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 7)

Unit: cd

G\C	C200.0	C210.0	C220.0	C230.0	C240.0	C250.0	C260.0	C270.0	C280.0	C290.0
G37.0	6.4	6.4	6.6	7.2	7.5	7.6	4.8	4.9	5.5	6.0
G38.0	5.7	5.1	4.6	6.1	6.7	5.9	3.8	5.1	4.0	5.3
G39.0	4.9	4.1	4.0	4.4	5.5	5.4	3.2	4.2	3.3	3.8
G40.0	4.2	3.4	4.0	4.3	4.3	3.9	1.8	3.2	2.5	3.2
G41.0	3.7	1.9	3.5	3.9	3.9	2.9	1.1	2.5	1.8	2.3
G42.0	2.9	2.0	2.1	2.7	2.5	2.1	1.2	1.5	0.9	2.1
G43.0	1.7	1.6	1.5	2.2	2.0	1.7	0.7	1.4	0.0	1.1
G44.0	0.5	1.0	1.6	1.1	1.8	1.2	0.0	0.9	0.0	0.7
G45.0	0.0	0.9	1.5	0.0	1.9	0.7	0.0	0.3	0.0	0.0
G46.0	0.3	0.3	1.1	0.0	0.5	0.9	0.0	0.0	0.0	0.1
G47.0	0.7	0.0	0.9	0.0	0.0	0.5	0.0	0.0	0.0	0.0
G48.0	0.0	0.0	0.0	0.0	0.0	0.2	0.0	0.0	0.0	0.0
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 9)

Unit: cd

G\C	C300.0	C310.0	C320.0	C330.0	C340.0	C350.0	C360.0			
G0.0	3671.2	3630.0	3635.8	3628.8	3628.6	3631.9	3655.1			
G1.0	3676.5	3658.9	3646.4	3631.9	3611.8	3605.6	3624.5			
G2.0	3646.9	3644.6	3612.3	3588.3	3550.2	3532.4	3545.3			
G3.0	3573.2	3581.6	3525.2	3477.5	3417.3	3386.4	3379.9			
G4.0	3436.3	3444.6	3360.9	3309.6	3232.1	3185.1	3156.0			
G5.0	3224.4	3231.9	3128.3	3068.4	2967.1	2901.9	2841.9			
G6.0	2932.8	2906.4	2782.3	2729.8	2609.3	2529.8	2451.4			
G7.0	2600.9	2558.2	2417.4	2345.1	2206.3	2130.1	2038.1			
G8.0	2163.4	2156.6	1991.1	1951.4	1762.5	1723.9	1614.1			
G9.0	1764.0	1725.2	1585.0	1520.6	1370.6	1300.5	1216.9			
G10.0	1367.0	1334.1	1227.3	1154.3	1041.9	976.5	906.6			
G11.0	1007.4	982.3	885.1	837.3	730.5	685.1	618.5			
G12.0	730.8	726.3	640.6	594.7	517.2	471.4	432.6			
G13.0	528.5	519.1	460.2	421.7	353.5	325.5	295.7			
G14.0	358.7	363.0	319.1	283.2	238.3	216.0	203.2			
G15.0	256.6	260.1	233.0	205.6	173.4	157.6	149.8			
G16.0	182.5	191.9	166.1	153.1	126.1	119.5	111.4			
G17.0	136.8	137.8	125.7	112.9	99.3	91.6	89.4			
G18.0	104.9	105.5	98.0	90.4	80.2	75.3	73.4			
G19.0	82.2	81.9	78.1	72.6	65.2	62.0	62.6			
G20.0	68.2	66.4	65.0	60.7	56.1	53.8	53.6			
G21.0	56.9	55.8	55.9	52.8	48.8	46.4	46.3			
G22.0	48.6	46.8	47.4	44.5	40.9	39.8	40.0			
G23.0	41.1	40.2	41.0	37.5	35.4	34.6	34.8			
G24.0	35.7	35.0	34.8	32.9	29.8	30.1	30.5			
G25.0	30.3	30.2	30.3	28.1	26.2	26.5	27.2			
G26.0	26.5	25.5	26.9	24.6	22.9	22.7	23.5			
G27.0	23.1	22.6	21.0	21.8	20.8	20.0	21.0			
G28.0	19.8	19.2	18.6	19.8	16.9	17.5	18.6			
G29.0	18.2	16.7	16.4	17.0	15.4	15.9	17.3			
G30.0	17.2	13.9	13.6	14.1	13.3	13.3	14.7			
G31.0	15.4	12.3	11.9	12.8	11.1	12.0	13.6			
G32.0	13.6	10.1	10.1	11.5	9.5	9.8	11.9			
G33.0	12.4	9.2	7.7	8.9	8.3	8.9	10.4			
G34.0	10.8	7.5	8.1	7.8	6.6	7.0	8.6			
G35.0	9.6	6.4	6.1	7.3	5.2	6.1	7.5			
G36.0	8.0	4.9	4.9	6.1	4.3	5.8	6.4			

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 10)

Unit: cd

G\C	C300.0	C310.0	C320.0	C330.0	C340.0	C350.0	C360.0			
G37.0	7.0	3.9	3.8	5.4	3.0	4.3	5.1			
G38.0	5.6	2.4	3.1	3.8	2.3	3.2	4.0			
G39.0	5.1	3.7	2.6	3.3	2.0	3.0	3.8			
G40.0	4.2	3.0	1.4	2.0	0.9	2.2	2.4			
G41.0	3.3	1.3	0.8	1.4	0.1	1.5	1.7			
G42.0	2.3	0.5	0.5	0.9	0.0	0.3	1.0			
G43.0	1.7	0.4	0.0	0.4	0.0	0.0	1.3			
G44.0	1.6	0.0	0.0	0.1	0.0	0.0	0.3			
G45.0	1.7	0.0	0.0	0.0	0.0	0.0	0.0			
G46.0	1.2	0.0	0.0	0.0	0.0	0.0	0.0			
G47.0	0.9	0.0	0.0	0.0	0.0	0.0	0.0			
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

