



Report No.:

Test Time: 2021-04-12 11:01

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: RAD-S-CIS-3.5000.24.-.12

Luminous Length (mm): -53

Luminous Width (mm): -53

Luminous Height (mm): 70

Voltage: 24.0 V

Current: 0.151 A

Power: 3.63 W

Power Factor: 1.000

Photometric Results

CIE Class: Direct

Measurement Flux: 269.4 lm

Downward Ratio: 100%

Total Rated Lamp Lumens: 269.4 lm

Efficiency: 100%

Upward Ratio: 0%

Field Angle(C0/C180,C90/C270,C45/C225,C135/315): 24.6, 24.6, 25.1, 25.0

Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 14.6, 14.7, 14.7, 14.5

Luminaire Efficacy Rating (LER): 74.27

Central Intensity: 3595.63 cd


Max. Intensity: 3642.87 cd

Pos of Max. Intensity: H280 V1


S/MH(C0/C180): 0.25

S/MH(C90/C270): 0.26

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 10.0

Test Lab: Svet-lab

Test Type: TYPE C

Temperature:

Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0


Test Device: LSG-1700B

Distance: 9.600 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve




C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)




Isocandela (rectangle)



Imax (100%): 3643 cd

(10%): 364 cd	(16%): 583 cd
(25%): 911 cd	(40%): 1457 cd
(63%): 2295 cd	(100%): 3643 cd

IsoLux Plot




Mounting Height: 10.0m Max Lux(100%): 36.4 lx

(1%): 0.4 lx	(2%): 0.7 lx
(5%): 1.8 lx	(10%): 3.6 lx
(20%): 7.3 lx	(50%): 18.2 lx
(100%): 36.4 lx	


C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 3595.6 lx
 (1%): 36.0 lx (2%): 71.9 lx
 (5%): 179.8 lx (10%): 359.6 lx
 (20%): 719.1 lx (50%): 1797.8 lx
 (100%): 3595.6 lx

C Plane (°): 0.0-360.0: 10.0
 Test Lab: Svet-lab
 Test Type: TYPE C
 Temperature:
 Operator: Svet-lab

Gamma Plane (°): 0.0-90.0: 1.0
 Test Device: LSG-1700B
 Distance: 9.600 m
 Humidity:
 Inspector:

The Average Illuminance Effective Figure




UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
3H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=4H Y=2H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
3H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=8H Y=4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=12H Y=4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
Variations with the observer position at spacings:										
S=1.0H	-1.\$/6.9					-1.\$/6.9				
S=1.5H	-1.\$/9.7					-1.\$/9.7				
S=2.0H	-1.\$/11.7					-1.\$/11.7				

Calculate in accordance with CIE Pub.117. The table is revised with 269lm ($8\log(F/F_0) = -4.6$).

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM




ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	113	41.8
FL (0°-30°)	111	41.3
FM (30°-60°)	1	0.5
FH (60°-80°)	0	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	157	58.2
BL (0°-30°)	155	57.5
BM (30°-60°)	2	0.7
BH (60°-80°)	0	0.0
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

LCS Graph



Back Light

Scale= MAX LCS%

Trapped Light:NA,NA

Forward Light

C Plane (°):0.0-360.0: 10.0

Test Lab: Svet-lab

Test Type: TYPE C

Temperature:

Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0

Test Device: LSG-1700B

Distance: 9.600 m

Humidity:

Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	3543.1	3.4	3.4	1.26	1.26
1.0-2.0	3477.0	10.0	13.4	3.70	4.96
2.0-3.0	3336.4	16.0	29.3	5.92	10.89
3.0-4.0	3123.9	20.9	50.2	7.76	18.65
4.0-5.0	2850.0	24.5	74.8	9.10	27.75
5.0-6.0	2504.4	26.3	101.1	9.77	37.52
6.0-7.0	2121.5	26.3	127.4	9.78	47.30
7.0-8.0	1735.0	24.8	152.3	9.22	56.51
8.0-9.0	1358.6	22.0	174.3	8.17	64.69
9.0-10.0	1029.8	18.6	192.9	6.92	71.61
10.0-11.0	750.9	15.0	207.9	5.57	77.18
11.0-12.0	530.6	11.6	219.5	4.31	81.48
12.0-13.0	376.3	8.9	228.5	3.32	84.80
13.0-14.0	265.1	6.8	235.2	2.52	87.32
14.0-15.0	189.2	5.2	240.4	1.93	89.24
15.0-16.0	139.7	4.1	244.5	1.52	90.76
16.0-17.0	105.5	3.3	247.8	1.22	91.98
17.0-18.0	82.8	2.7	250.6	1.01	93.00
18.0-19.0	66.6	2.3	252.9	0.86	93.86
19.0-20.0	55.0	2.0	254.9	0.75	94.61
20.0-21.0	46.5	1.8	256.7	0.66	95.27
21.0-22.0	39.5	1.6	258.3	0.59	95.86
22.0-23.0	33.7	1.4	259.7	0.52	96.38
23.0-24.0	28.9	1.3	260.9	0.47	96.85
24.0-25.0	24.7	1.1	262.1	0.42	97.27
25.0-26.0	21.3	1.0	263.1	0.37	97.64
26.0-27.0	18.5	0.9	264.0	0.34	97.98
27.0-28.0	16.1	0.8	264.8	0.30	98.28
28.0-29.0	14.0	0.7	265.5	0.27	98.55
29.0-30.0	12.1	0.7	266.2	0.24	98.79
30.0-31.0	10.4	0.6	266.8	0.22	99.01
31.0-32.0	9.0	0.5	267.3	0.19	99.20
32.0-33.0	7.6	0.4	267.7	0.17	99.37
33.0-34.0	6.4	0.4	268.1	0.14	99.51
34.0-35.0	5.3	0.3	268.4	0.12	99.63
35.0-36.0	4.3	0.3	268.7	0.10	99.73

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab


Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	3.4	0.2	268.9	0.08	99.82
37.0-38.0	2.7	0.2	269.1	0.07	99.88
38.0-39.0	2.0	0.1	269.2	0.05	99.93
39.0-40.0	1.3	0.1	269.3	0.03	99.96
40.0-41.0	0.7	0.1	269.4	0.02	99.98
41.0-42.0	0.4	0.0	269.4	0.01	99.99
42.0-43.0	0.1	0.0	269.4	0.00	100.00
43.0-44.0	0.0	0.0	269.4	0.00	100.00
44.0-45.0	0.0	0.0	269.4	0.00	100.00
45.0-46.0	0.0	0.0	269.4	0.00	100.00
46.0-47.0	0.0	0.0	269.4	0.00	100.00
47.0-48.0	0.0	0.0	269.4	0.00	100.00
48.0-49.0	0.0	0.0	269.4	0.00	100.00
49.0-50.0	0.0	0.0	269.4	0.00	100.00
50.0-51.0	0.0	0.0	269.4	0.00	100.00
51.0-52.0	0.0	0.0	269.4	0.00	100.00
52.0-53.0	0.0	0.0	269.4	0.00	100.00
53.0-54.0	0.0	0.0	269.4	0.00	100.00
54.0-55.0	0.0	0.0	269.4	0.00	100.00
55.0-56.0	0.0	0.0	269.4	0.00	100.00
56.0-57.0	0.0	0.0	269.4	0.00	100.00
57.0-58.0	0.0	0.0	269.4	0.00	100.00
58.0-59.0	0.0	0.0	269.4	0.00	100.00
59.0-60.0	0.0	0.0	269.4	0.00	100.00
60.0-61.0	0.0	0.0	269.4	0.00	100.00
61.0-62.0	0.0	0.0	269.4	0.00	100.00
62.0-63.0	0.0	0.0	269.4	0.00	100.00
63.0-64.0	0.0	0.0	269.4	0.00	100.00
64.0-65.0	0.0	0.0	269.4	0.00	100.00
65.0-66.0	0.0	0.0	269.4	0.00	100.00
66.0-67.0	0.0	0.0	269.4	0.00	100.00
67.0-68.0	0.0	0.0	269.4	0.00	100.00
68.0-69.0	0.0	0.0	269.4	0.00	100.00
69.0-70.0	0.0	0.0	269.4	0.00	100.00
70.0-71.0	0.0	0.0	269.4	0.00	100.00
71.0-72.0	0.0	0.0	269.4	0.00	100.00

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:



C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C10.0	C20.0	C30.0	C40.0	C50.0	C60.0	C70.0	C80.0	C90.0
G0.0	3595.6	3596.8	3595.7	3591.8	3600.2	3588.6	3598.0	3582.6	3593.8	3575.6
G1.0	3573.6	3550.4	3539.9	3514.4	3513.5	3486.6	3487.9	3471.4	3477.6	3461.7
G2.0	3485.2	3443.4	3420.7	3382.3	3368.9	3339.3	3329.6	3304.0	3307.7	3292.0
G3.0	3315.1	3257.8	3225.5	3155.4	3141.5	3083.4	3080.0	3026.5	3038.5	3006.1
G4.0	3097.5	3002.2	2970.0	2880.4	2855.3	2767.1	2755.9	2704.0	2716.6	2654.0
G5.0	2783.4	2661.4	2623.2	2522.5	2499.1	2413.9	2396.8	2319.4	2324.1	2275.0
G6.0	2386.6	2250.2	2211.2	2109.1	2084.6	1974.5	1954.2	1893.2	1898.9	1827.1
G7.0	1978.2	1841.8	1805.3	1705.4	1682.3	1592.8	1575.4	1493.9	1501.5	1450.1
G8.0	1576.4	1434.6	1423.0	1307.5	1305.1	1195.4	1212.3	1122.3	1139.9	1062.7
G9.0	1191.0	1095.1	1058.6	973.0	969.8	902.6	889.9	823.1	823.3	785.8
G10.0	891.3	798.0	771.5	718.3	718.3	654.7	645.3	603.5	600.0	557.0
G11.0	611.3	555.7	538.9	497.7	497.6	460.2	454.4	420.7	408.9	383.8
G12.0	427.9	385.2	382.4	358.9	361.9	331.7	330.4	302.3	295.2	274.7
G13.0	298.4	272.1	272.0	258.3	260.2	245.5	242.8	222.1	216.3	203.3
G14.0	208.9	193.7	192.1	187.9	190.8	177.7	178.6	163.4	158.8	147.2
G15.0	153.9	144.1	144.7	141.2	143.8	134.8	134.7	123.9	120.2	111.2
G16.0	116.1	109.2	109.0	105.4	107.4	99.2	101.9	95.1	91.8	84.9
G17.0	90.4	86.9	84.2	82.3	84.0	78.6	80.6	75.3	73.3	67.9
G18.0	73.3	70.0	68.5	67.3	68.2	61.9	65.5	62.9	60.3	56.2
G19.0	60.8	57.8	55.4	55.8	55.5	50.5	53.5	51.7	50.6	46.9
G20.0	50.7	49.4	47.4	46.5	46.0	43.0	45.0	44.0	43.1	40.5
G21.0	43.6	41.5	40.2	39.1	39.5	35.5	38.5	36.7	37.5	33.8
G22.0	37.3	35.5	33.8	33.9	33.5	30.3	32.8	32.1	31.1	28.7
G23.0	32.6	31.1	29.0	29.3	29.3	25.8	27.7	28.0	27.0	24.9
G24.0	27.5	26.9	24.3	25.1	25.0	22.1	24.5	23.8	23.6	21.5
G25.0	23.6	23.4	20.2	21.1	21.7	19.0	20.8	20.6	21.0	18.5
G26.0	20.4	20.5	18.0	19.2	18.8	16.4	18.0	17.8	17.3	15.3
G27.0	17.4	17.5	15.9	16.7	16.5	14.1	16.2	15.8	15.2	13.3
G28.0	15.1	15.6	15.2	13.9	15.1	12.0	13.9	13.7	12.7	11.5
G29.0	13.9	13.4	13.1	12.4	13.1	9.6	12.8	12.7	11.3	9.8
G30.0	11.6	12.3	11.9	11.3	10.4	7.9	10.8	10.8	10.1	8.4
G31.0	10.5	10.3	9.8	9.3	9.7	7.2	8.8	9.4	8.7	7.1
G32.0	8.3	8.9	8.8	8.1	8.1	6.1	8.1	8.8	7.3	5.3
G33.0	7.6	7.5	7.1	6.6	6.3	4.8	7.6	6.9	5.7	4.8
G34.0	6.5	7.1	6.2	5.6	5.5	3.6	5.6	5.9	5.3	3.1
G35.0	5.2	6.1	5.2	5.0	4.5	3.0	5.5	4.4	3.8	2.4
G36.0	4.1	5.0	4.9	3.7	3.8	2.7	3.5	3.8	3.0	2.2

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C10.0	C20.0	C30.0	C40.0	C50.0	C60.0	C70.0	C80.0	C90.0
G37.0	2.7	4.4	3.4	3.5	3.2	1.2	2.0	3.3	2.6	1.5
G38.0	1.9	3.6	2.7	2.5	1.9	0.9	1.1	3.3	0.9	0.3
G39.0	2.0	2.6	1.6	1.8	1.3	1.5	0.8	2.4	1.0	0.1
G40.0	0.9	1.5	1.4	0.9	0.9	0.2	0.1	1.5	0.0	0.0
G41.0	0.0	0.9	0.0	0.3	0.7	0.3	0.0	1.4	0.0	0.0
G42.0	0.3	0.0	0.0	0.0	0.0	0.0	0.0	0.6	0.4	0.0
G43.0	0.0	0.3	0.0	0.0	0.0	0.0	0.2	0.0	0.0	0.0
G44.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 3)

Unit: cd

G\C	C100.0	C110.0	C120.0	C130.0	C140.0	C150.0	C160.0	C170.0	C180.0	C190.0
G0.0	3590.1	3576.5	3568.3	3491.0	3498.1	3479.2	3482.8	3477.6	3595.6	3596.8
G1.0	3475.9	3463.3	3452.3	3359.1	3385.5	3374.9	3397.9	3407.5	3549.8	3569.2
G2.0	3304.4	3285.6	3273.4	3151.5	3196.2	3193.4	3238.1	3264.8	3433.5	3477.5
G3.0	3035.2	3011.7	2997.2	2848.2	2913.9	2916.8	2996.2	3038.2	3243.5	3305.7
G4.0	2688.4	2670.3	2652.7	2489.6	2571.9	2599.2	2683.4	2744.1	2982.1	3084.0
G5.0	2307.8	2271.6	2275.4	2107.7	2200.3	2222.0	2336.9	2390.9	2658.6	2765.7
G6.0	1861.4	1844.3	1826.3	1671.7	1766.7	1811.7	1916.2	1974.6	2250.2	2371.9
G7.0	1483.7	1449.5	1459.0	1317.8	1408.2	1432.6	1548.6	1601.6	1839.6	1963.5
G8.0	1128.2	1084.7	1112.0	963.5	1068.9	1075.6	1190.3	1221.4	1427.2	1576.4
G9.0	813.9	802.4	804.8	707.8	776.4	801.1	870.6	906.9	1074.9	1174.6
G10.0	578.5	569.6	577.6	515.5	556.5	577.2	624.3	660.4	788.1	866.3
G11.0	399.7	394.2	405.7	363.8	400.0	404.1	441.3	449.3	527.7	591.9
G12.0	289.9	284.7	293.4	269.4	295.7	300.9	318.8	324.8	370.8	405.2
G13.0	211.4	213.0	220.9	203.7	224.3	224.4	236.3	236.5	262.5	286.2
G14.0	155.4	156.0	161.4	151.3	165.2	167.3	171.8	172.6	186.3	204.9
G15.0	118.3	119.4	123.9	116.1	126.8	126.1	132.0	128.5	140.1	150.1
G16.0	89.7	90.9	94.2	89.2	95.0	95.1	98.1	97.3	105.5	115.8
G17.0	71.5	73.2	75.3	71.2	76.3	76.1	77.7	77.2	83.3	88.6
G18.0	59.2	59.8	60.3	58.0	61.4	60.7	63.8	63.1	67.7	72.0
G19.0	49.3	49.5	49.4	48.3	49.9	49.6	51.8	52.0	54.4	58.7
G20.0	42.4	42.4	42.5	40.5	42.7	41.9	43.7	43.5	46.6	49.5
G21.0	35.9	35.5	35.6	34.2	36.1	35.0	35.4	36.9	39.4	43.2
G22.0	30.8	31.2	31.2	30.1	30.8	30.4	30.0	30.5	33.3	37.3
G23.0	26.5	26.6	26.9	25.7	27.0	26.0	24.7	26.3	28.6	31.6
G24.0	23.6	23.0	22.9	22.5	23.0	22.4	21.0	22.3	24.7	27.4
G25.0	20.3	19.9	19.8	19.2	20.1	19.2	18.2	19.4	21.3	23.8
G26.0	17.8	17.6	17.8	16.5	17.7	16.3	16.2	17.1	18.8	20.8
G27.0	14.7	15.3	15.6	14.9	15.1	14.8	14.3	14.7	16.3	18.2
G28.0	13.9	13.4	12.8	12.9	12.3	12.1	11.5	12.9	13.9	16.0
G29.0	11.7	11.0	11.8	10.5	10.2	11.1	9.8	10.8	12.0	14.2
G30.0	10.0	9.6	9.7	9.3	8.6	9.0	8.3	9.6	10.8	12.7
G31.0	8.4	8.7	8.6	8.4	7.4	7.8	6.9	7.6	9.3	11.3
G32.0	7.0	7.1	6.7	6.6	5.4	4.9	5.0	6.7	7.4	9.6
G33.0	6.4	6.3	6.2	5.3	4.5	4.5	4.0	5.0	6.3	8.4
G34.0	5.6	5.3	4.9	4.8	3.4	2.9	3.1	4.2	5.5	6.7
G35.0	4.1	4.6	3.8	4.2	2.8	2.0	2.3	3.3	3.8	5.8
G36.0	3.6	3.2	3.4	2.8	1.7	0.9	1.4	2.5	3.5	5.3

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 4)

Unit: cd

G\C	C100.0	C110.0	C120.0	C130.0	C140.0	C150.0	C160.0	C170.0	C180.0	C190.0
G37.0	2.8	2.3	3.2	2.5	1.1	0.2	0.5	2.0	2.1	4.4
G38.0	2.0	1.8	2.4	1.5	0.0	0.0	0.0	1.7	2.0	3.6
G39.0	1.1	1.4	1.2	0.8	0.0	0.0	0.0	0.8	0.8	2.8
G40.0	0.5	0.5	1.0	0.8	0.0	0.0	0.0	0.0	0.2	2.6
G41.0	0.1	0.0	0.2	0.0	0.0	0.0	0.0	0.0	0.0	1.5
G42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0
G43.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.4
G44.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.2
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 6)

Unit: cd

G\C	C200.0	C210.0	C220.0	C230.0	C240.0	C250.0	C260.0	C270.0	C280.0	C290.0
G0.0	3595.7	3591.8	3600.2	3588.6	3598.0	3582.6	3593.8	3575.6	3590.1	3576.5
G1.0	3576.6	3593.5	3604.7	3618.5	3626.1	3635.3	3642.3	3641.8	3642.9	3634.8
G2.0	3496.1	3530.0	3549.3	3578.2	3592.7	3611.8	3619.2	3629.1	3624.8	3619.9
G3.0	3334.6	3395.8	3421.3	3468.1	3484.2	3522.8	3525.5	3541.2	3527.3	3528.3
G4.0	3125.9	3195.9	3235.9	3303.3	3322.8	3367.6	3368.4	3399.2	3383.3	3385.8
G5.0	2818.5	2928.6	2973.2	3062.6	3088.4	3157.1	3157.6	3195.8	3171.6	3173.1
G6.0	2423.2	2540.1	2608.5	2710.9	2756.0	2841.4	2847.5	2875.0	2849.5	2860.0
G7.0	2038.1	2160.6	2206.3	2343.3	2381.2	2481.6	2469.6	2517.2	2468.8	2490.6
G8.0	1595.3	1757.5	1784.6	1953.2	1946.7	2072.6	2030.1	2119.6	2030.1	2099.1
G9.0	1220.8	1350.6	1390.0	1513.5	1554.4	1635.6	1614.8	1658.5	1631.5	1636.4
G10.0	908.5	1002.0	1053.1	1160.0	1181.3	1243.8	1237.5	1278.2	1241.9	1264.1
G11.0	627.2	700.4	745.8	818.9	850.2	895.4	866.9	894.8	887.3	898.5
G12.0	429.7	492.8	519.5	581.4	591.3	619.3	609.9	628.7	612.7	635.1
G13.0	302.4	341.1	360.5	407.9	412.9	428.0	411.8	433.1	422.0	433.5
G14.0	207.7	237.9	249.6	276.8	274.4	285.6	276.3	285.1	279.0	293.9
G15.0	154.9	173.6	184.0	201.4	198.1	203.4	195.8	201.9	198.5	208.4
G16.0	115.3	131.5	132.6	148.4	143.0	149.7	140.2	147.0	142.6	150.6
G17.0	89.2	98.2	102.7	110.9	109.9	111.0	106.9	109.0	109.0	114.1
G18.0	71.5	78.1	80.8	86.6	86.4	87.9	84.3	86.6	86.7	89.3
G19.0	57.0	63.6	65.6	68.7	68.1	70.1	68.6	68.7	69.5	72.2
G20.0	49.2	54.1	55.1	57.5	56.3	59.3	57.8	58.3	59.0	60.5
G21.0	41.8	46.3	46.4	49.4	48.0	48.6	49.2	50.8	51.2	52.3
G22.0	35.0	38.5	39.5	40.5	40.8	41.0	42.0	41.6	43.0	43.6
G23.0	29.9	33.1	34.3	35.3	35.2	34.6	35.5	35.2	36.7	37.8
G24.0	25.2	28.6	29.3	30.4	29.8	29.8	30.6	29.6	31.7	32.6
G25.0	20.9	24.1	24.9	25.4	26.0	25.0	25.7	24.9	27.1	27.7
G26.0	18.7	21.0	22.2	21.9	21.6	21.9	22.3	22.2	23.7	24.5
G27.0	15.4	18.4	19.4	18.9	18.9	18.8	19.4	18.4	20.1	20.1
G28.0	13.6	16.0	16.5	16.5	16.9	16.7	16.5	16.0	17.6	18.0
G29.0	11.3	13.8	14.8	14.1	14.4	14.1	14.6	13.8	16.1	15.5
G30.0	9.6	11.9	13.0	12.0	12.4	11.8	13.2	11.4	13.6	13.1
G31.0	8.4	10.0	11.3	10.1	11.0	10.6	11.3	11.5	11.5	11.5
G32.0	7.6	8.8	10.0	8.3	9.6	8.7	9.7	9.7	9.9	10.0
G33.0	5.7	7.5	8.4	7.2	8.2	7.7	8.6	7.6	9.1	8.3
G34.0	4.3	6.7	6.6	7.5	6.1	5.9	7.7	6.8	7.2	7.0
G35.0	2.9	5.0	5.0	5.4	5.2	5.3	6.5	6.6	6.1	5.8
G36.0	2.4	4.5	4.5	4.6	4.6	4.4	5.5	4.9	5.5	5.0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 7)

Unit: cd

G\C	C200.0	C210.0	C220.0	C230.0	C240.0	C250.0	C260.0	C270.0	C280.0	C290.0
G37.0	1.5	3.6	3.3	3.6	3.8	3.4	4.5	4.0	4.6	4.1
G38.0	0.4	2.5	3.0	2.3	2.6	2.7	3.2	3.8	4.0	3.6
G39.0	0.9	1.8	1.7	2.0	1.8	1.5	2.3	3.1	3.1	2.7
G40.0	0.2	0.5	1.1	1.0	1.0	0.9	1.7	2.4	2.3	2.0
G41.0	0.3	0.0	0.8	0.7	0.8	0.0	1.1	1.5	1.9	1.5
G42.0	0.0	0.0	0.5	0.0	0.5	1.0	0.7	0.3	1.1	0.9
G43.0	0.0	0.0	0.0	0.0	0.0	0.3	0.0	0.0	0.3	0.0
G44.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 9)

Unit: cd

G\C	C300.0	C310.0	C320.0	C330.0	C340.0	C350.0	C360.0			
G0.0	3568.3	3491.0	3498.1	3479.2	3482.8	3477.6	3595.6			
G1.0	3619.5	3563.1	3544.0	3520.1	3493.2	3473.0	3573.6			
G2.0	3606.5	3572.4	3531.4	3494.6	3445.4	3409.5	3485.2			
G3.0	3509.3	3500.8	3442.9	3389.8	3322.4	3267.4	3315.1			
G4.0	3360.5	3368.2	3288.8	3233.5	3136.9	3060.8	3097.5			
G5.0	3144.0	3169.9	3062.7	3004.9	2865.4	2768.9	2783.4			
G6.0	2826.1	2884.8	2746.9	2663.7	2507.3	2396.1	2386.6			
G7.0	2458.8	2532.6	2374.7	2306.0	2140.7	2026.7	1978.2			
G8.0	2031.6	2155.5	1953.3	1903.4	1700.8	1632.4	1576.4			
G9.0	1615.1	1714.6	1576.6	1475.3	1343.8	1248.3	1191.0			
G10.0	1250.9	1346.0	1205.3	1132.3	1011.2	933.3	891.3			
G11.0	907.6	974.3	874.8	816.9	721.2	658.8	611.3			
G12.0	637.6	708.3	634.6	585.5	502.6	462.0	427.9			
G13.0	444.3	500.3	443.7	409.2	356.2	320.8	298.4			
G14.0	297.9	338.2	301.3	282.8	244.4	225.9	208.9			
G15.0	211.9	242.7	218.3	204.0	179.3	164.4	153.9			
G16.0	151.6	174.4	157.5	153.4	132.6	125.2	116.1			
G17.0	113.8	128.4	121.0	113.6	104.7	95.1	90.4			
G18.0	89.8	98.8	94.0	89.9	82.7	76.6	73.3			
G19.0	70.8	78.0	74.3	71.4	66.4	62.5	60.8			
G20.0	59.3	64.2	61.5	59.2	56.3	53.9	50.7			
G21.0	49.4	54.8	52.8	50.9	48.3	45.3	43.6			
G22.0	41.8	46.0	44.7	43.0	41.4	38.0	37.3			
G23.0	35.5	39.6	38.4	36.3	35.3	32.8	32.6			
G24.0	29.8	33.5	31.6	31.3	29.9	29.2	27.5			
G25.0	25.2	28.9	27.6	26.8	25.4	24.1	23.6			
G26.0	21.4	25.1	24.2	23.0	22.2	22.0	20.4			
G27.0	18.2	21.4	21.2	19.9	19.6	18.7	17.4			
G28.0	15.8	19.2	18.7	17.4	16.5	15.6	15.1			
G29.0	13.2	16.7	16.2	15.4	14.1	13.8	13.9			
G30.0	11.3	14.1	13.8	13.2	12.6	11.5	11.6			
G31.0	9.6	13.2	11.3	11.8	11.3	11.2	10.5			
G32.0	8.4	10.9	9.6	10.2	9.7	9.5	8.3			
G33.0	6.7	10.4	8.4	8.4	8.3	8.0	7.6			
G34.0	5.4	9.6	7.0	7.3	6.8	6.8	6.5			
G35.0	3.8	7.8	5.5	5.4	6.3	5.4	5.2			
G36.0	3.9	5.5	4.3	4.4	4.7	4.1	4.1			

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

Candlepower Table (Continue 10)

Unit: cd

G\C	C300.0	C310.0	C320.0	C330.0	C340.0	C350.0	C360.0			
G37.0	3.0	5.5	4.3	3.8	3.8	3.9	2.7			
G38.0	2.0	5.0	4.0	3.2	3.3	2.6	1.9			
G39.0	1.3	3.0	2.6	2.2	2.5	2.0	2.0			
G40.0	0.5	2.2	1.9	1.2	2.4	1.3	0.9			
G41.0	0.2	0.3	1.2	0.5	1.3	0.9	0.0			
G42.0	0.0	0.0	0.8	0.0	0.2	0.6	0.3			
G43.0	0.0	0.0	0.0	0.0	0.3	0.0	0.0			
G44.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0			
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 10.0
Test Lab: Svet-lab
Test Type: TYPE C
Temperature:
Operator: Svet-lab

Gamma Plane (°):0.0-90.0:1.0
Test Device: LSG-1700B
Distance: 9.600 m
Humidity:
Inspector:

